

PVC					PE-HD/PP-H/PPs/PP-EL- s/PVDF				Wandstärke Rohr s			
Ø	L	L1	A	s	L	L1	A	PPs	PP-H	PE-HD	PP-el-s	
90	40	140	65	1,8	40	140	65	3,0	2,7	3,4	-	
110	40	160	65	1,8	40	160	65	3,0	2,7	3,4	-	
125	40	165	65	1,8	40	165	65	3,0	3,1	3,9	-	
140	40	170	65	1,8	40	170	65	3,0	3,5	4,3	-	
160	40	180	65	1,8	40	180	65	3,0	4,0	4,0	3,0	
180	40	190	65	1,8	40	190	65	3,0	4,4	5,5	3,0	
200	40	200	65	1,8	40	200	65	3,0	3,0	6,2	3,0	
225	40	210	65	1,8	40	210	65	3,5	5,5	6,9	3,5	
250	40	225	65	2,0	40	225	65	3,5	3,5	6,2	3,5	
280	50	240	75	2,3	50	240	75	3,5	6,9	8,6	3,5	
315	50	260	75	2,5	50	260	75	5,0	5,0	7,7	5,0	
355	50	280	75	2,9	50	280	75	5,0	5,0	10,9	5,0	
400	50	300	75	3,2	50	300	75	6,0	6,0	12,3	6,0	
450	50	340	75	3,6	50	340	75	5,0	5,0	5,0	5,0	
500	50	380	75	4,0	50	380	75	5,0	5,0	5,0	5,0	

560	-	-	-	-	60	420	85	6,0	6,0	6,0	6,0
600	60	450	85	5,0	60	450	85	6,0	6,0	6,0	6,0
630	-	-	-	-	70	480	95	6,0	6,0	6,0	6,0
700	70	530	95	6,0	70	530	95	6,0	6,0	6,0	6,0
710	-	-	-	-	80	540	105	6,0	6,0	6,0	6,0
800	80	600	105	8,0	80	600	105	8,0	8,0	8,0	8,0
900	90	680	115	8,0	90	680	115	8,0	8,0	8,0	8,0
1000	100	750	125	10,0	100	750	125	10,0	10,0	10,0	10,0
1200	120	900	135	12,0	120	900	135	12,0	12,0	12,0	12,0
1250	130	940	145	12,0	130	940	145	12,0	12,0	12,0	12,0

Lamellen Ausführung 2 und 3 aus PVC; Luftgeschwindigkeit max. 10 m/sec.

*PP-EL-s erst ab Größe Ø 160mm lieferbar